

**Products Specification**

**SHENZHEN ABT ELECTRONICS CO., LTD.**

E-mail:sales@abt-power.com Web:www.abt-power.com

<b>SPECIFICATION</b>		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :	2011-01-10			
COMMON/UNITE	DOC. NO:		REV.: 2.0	PAGE: 1 OF 1

3PN0520S SMART NIMH BATTERY CHARGER				
NO	ITEM	UNIT	SPECIFICATION	REMARK
<b>INPUT</b>				
01	RATING INPUT	V ac	100~240Vac 50/60Hz	
02	INPUT RANGE	V ac	90~264Vac	
03	RATING INPUT CURRENT	A	0.1Arms	INPUT:230V OUTPUT:Full load
04	MAX. INPUT POWER	W	6	
<b>OUTPUT</b>				
05	RATING OUTPUT VOLTAGE	V dc	16Vdc	
06	OUTPUT VOLTAGE RANGE	V dc	7 ~ 22Vdc	22V is open circuit voltage
07	SUIT WITH BATTERY	Ah	8.4~12V 0.3~2.4Ah NIMN/NICD	
08	CHARGE CURRENT	A	0.30A ± 0.03A	
09	TRICKLE CURRENT	A	<0.05	
11	INNER TIMMER(default)	hour	8	Defined by user
12	MAX. OUTPUT POWER	W	5W	
13	HOLD-ON TIME	ms	NC	Input: 230Vac Output: Full load
14	RIPPLE CURRENT	mA	20	Input: 230Vac Output: Full load
15	MAIN CHARGE END CONDITION		-ΔV > 5mV /CELL(TYP) or VMAX>=1.6V/cell or Timer out.	
16	LED INDICATION		RED: MAIN CHARGE GREEN: FINISHED	
17	Output Short-circuit Protection Output Reverse Protection	-	YES NO	
18	EFFICIENCY	%	75%	At max. load
<b>ENVIRONMENT</b>				
19	OPERATE TEMP.	°C	-10 ~ +40	Full load & natural convection.
20	OPERATE HUMIDITY	%RH	< +90	Relative humidity, non-condensing.
21	STORAGE TEMP.	°C	-40 ~ +70	
22	STORAGE HUMIDITY	%RH	0 ~ +95	Relative humidity, non-condensing.
23	COOLING	-	Natural convection	
24	TEMP. FACT	%	--	
25	VIBRATION		5MM/50HZ/600S	Non-operating condition.
26	IMPACT		1 meter drop test >= 3 times	Non-operating condition.
<b>MECHANICAL</b>				
27	WEIGHT	g	100	
28	SIZE	mm	65X61X25	Casing only
29	DC Cable & CONNECTER	-	Defined by user	
<b>SAFETY</b>				
30	TEMP. RISE	°C	< 40 on casing	At any line and Max. Load
31	SAFETY STANDARD	-	EN60335 or EN60950	
32	EMC	-	EN55013 or EN55022B	
33	MTBF	hrs	30000	
34	ESD	kV	8.0	
35	HI-POT	V	i/p to o/p: 3000 (1 min.)	For final unit, cut-off current =10mA